




SPARK PLUGS

Our Part Number	Picture	DESCRIPTION	Stocked
B8ES		14mm SPARK PLUG	*
BR8E1X		14mm SPARK PLUG-IRIDIUM	*
BR8ES		SPARK PLUG-NGK RESISTOR PLUG	*
DCPR7E		12mm NGK SPARK PLUG	*
DCPR8E		12mm SPARK PLUG-NGK 912 ULS	*
DP9EA-9		12mm NGK SPARK PLUG 914	*
HSR86		LODGE Spark Plug	*
R33S		AC Plug	*
SR44E		AC PLUG	*
Part No difference is the letter "U" in the prefix for Tempest plugs			
R37S-1		Champion Plug	*
REB32N		Champion Plug OR UREB32N TEMPEST	*
REB37E		Champion Plug OR UREB37E TEMPEST	*
REM37B		Champion Plug ONLY for Gipsy engine with Slick Mags	*
REM37BY		Champion Plug OR UREM37BY TEMPEST	*
REM38E		Champion Plug OR UREM38E TEMPEST	*
REM40E		Champion Plug OR UREM40E TEMPEST	*
REM40EA		Champion Plug OR UREM40EA TEMPEST	*
RHB32E		Champion Plug OR URHB32E TEMPEST	*
RHB37E		Champion Plug OR URHB37E TEMPEST	*
RHB37N		Champion Plug OR URHB37N TEMPEST	*
RHM38E		Champion Plug OR URHM38E TEMPEST	*
RHM40E		Champion Plug OR URHM40E TEMPEST	*

ACCESSORIES

Our Part Number	Picture	DESCRIPTION	Stocked
T556		Spark Plug Thread Lubricant and Anti-Seize Compound helps to prevent galling and lubricates threads during installation.	*

SPARK PLUGS & IGNITION ACCESSORIES

E-Mail: sales@asapspares.com.au

Our Part Number	Picture	DESCRIPTION	Stocked
VD05FMH		Old type suppressed plug connector Rotax 4 stroke 912(s) and 914.	*
LB05F		NGK SPARK PLUG CAP	*
AN 4027-1		These are the 18mm copper spark plug gaskets.	*
AN 4060-1		Protector ignition cable Plastic; red; 1.410 in. long; 0.560 inches. diameter 5/8 X 24NF TPI thread	*
12Y-01683		Chaser cleans threads in spark plug hole of dirt, carbon build-up, and metal particles. Double ended for both 14mm and 18mm threads. Neoprene band on hex drive holds tool securely in any 13/16" deep-well spark plug socket.	*
265-240		New suppressed plug connector Rotax 4 stroke 912(s) and 914.	*

***Carried on shelf**