FUEL WARNING SYSTEM
&
FLEXIBLE RUBBER FUEL LINE

E-Mail: sales@asapspares.com.au

FUEL WARNING SENSOR

Our Part Number	Description
6905- 400	Float-action sensor in tank activates panel warning light when fuel supply is low. All-PBT unit, impervious to aviation fuel. Use **AN 867-4** flange for mounting.

FLEXIBLE RUBBER FUEL LINE HOSE

Parker's fuel line hose includes a new thermoplastic barrier that helps protect our atmosphere from harmful hydrocarbons that escape through the carcass of ordinary fuel hose. This new hose surpasses all of CARB's stringent permeation requirements and is similar to SAE30R7 specifications. The Super-Flex FL hose also features an abrasion and weather resistant cover to help protect from external application abuse.
Approved for biodiesel fuels that meet ASTM D 6751 requirements per UL guidelines for Biodiesel compatibility.
4:1 Design factor

Our Part Number	ID	OD	MAX Working Press
MILH6000-1/4	1/4	1/2	1000
MILH6000-5/16	5/16		1000
MILH6000-3/8	3/8	5/8	1000
MILH6000-1/2	1/2		1000
MILH6000-3/4	3/4		1000
MILH6000-1.000	1”		1000
MILH6000-1.500”	1.5”		1000

- Tube: NBR with a thermoplastic barrier
- Cover: Black Hypalon
- Reinforcement: Braided Polyester
- Temperature Range: -30°F to +257°F (-34°C to +125°C)

All measurements are Imperial