

CABLE EYE END-FLYING CONTROLS (SHACKLE END)

E-Mail: sales@asapspares.com.au
All measurements are Imperial

401

Picture Description	Our Part Number	Alternate Part Number	Hole Diameter	Wire Rope Diameter	Max Breaking Strength LBS	Length	Thread Size
	MS21255C2LL	AN170-8LL	0.188	1/16"	800	1 3/4	6-40
	MS21255C2RL	AN170-8RL	0.188	1/16"	800	1 3/4	6-40
	MS21255C2LS	AN170-8LS	0.188	1/16"	800	1 1/2	6-40
	MS21255C2RS	AN170-8RS	0.188	1/16"	800	1 1/2	6-40
	MS21255C3LL	AN170-16LL	0.219	3/32"	1600	2 1/2	10-32
	MS21255C3RL	AN170-16RL	0.219	3/32"	1600	2 1/2	10-32
	MS21255C3LS	AN170-16LS	0.219	3/32"	1600	1 5/8	10-32
	MS21255C3RS	AN170-16RS	0.219	3/32"	1600	1 5/8	10-32
	MS21255C5LL	AN170-22LL	0.219	5/32"	3200	2 5/8	1/4-28
	MS21255C5RL	AN170-22RL	0.219	5/32"	3200	2 5/8	1/4-28
	MS21255C5LS	AN170-22LS	0.219	5/32"	3200	1 3/4	1/4-28
	MS21255C5RS	AN170-22RS	0.219	5/32"	3200	1 3/4	1/4-28
	MS21255C5LL	AN170-32LL	0.281	5/32"	3200	2 5/8	1/4-28
	MS21255C5RL	AN170-32RL	0.281	5/32"	3200	2 5/8	1/4-28
	MS21255C5LS	AN170-32LS	0.281	5/32"	3200	1 3/4	1/4-28
	MS21255C5RS	AN170-32RS	0.281	5/32"	3200	1 3/4	1/4-28
	MS21255C6LL	AN170-46LL	0.328	3/16"	4600	2 3/4	5/16-24
	MS21255C6RL	AN170-46RL	0.328	3/16"	4600	2 3/4	5/16-24
	MS21255C6LS	AN170-46LS	0.328	3/16"	4600	1 7/8	5/16-24
	MS21255C6RS	AN170-46RS	0.328	3/16"	4600	1 7/8	5/16-24

Other items that may be of interest

